zencontrol

Wireless zhaga long range microwave **datasheet**



1300 943 233 info@lumenresources.com.au lumenresources.com.au



Features

Powered from 12-24Vdc aux supply Inbuilt microwave and light sensor Configurable microwave sensitivity Compatible with Zhaga (Book 18) Wireless support for IEC62386-104 over Thread®



Converts luminaires

Converts 0-10V luminaires to wireless smart luminaires



Long range sensing

8m range when mounted at 10 metres.



IEC62386-104 over Thread®

Works with products supporting IEC 62386-104 over Thread®



Compatible

Wireless control system solution for luminaires with Zhaga Book 18 socket.

zencontrol

Wireless zhaga long range microwave datasheet



1300 943 233 info@lumenresources.com.au lumenresources.com.au




Product range

Order code	Description
zc-z10-mw-ulr	Zhaga long range microwave sensor and wireless 0-10V control interface

Features


- Powered from 12-24Vdc aux supply
- Supports IEC 62386-104 over Thread®
- Inbuilt microwave and light sensor
- Configurable microwave sensitivity
- Compatible with Zhaga (Book 18)
- A wireless control system solution for 0-10V luminaires
- Standalone configuration with zencontrol express

Dimensions



Installation requirements

- For optimal detection performance, mount the sensor at a height of 2.7 m. Ensure there is a clear space of 1.5 m on each side (tangential direction) and 1.5 m in front of the sensor (radial direction).
- Avoid installing the sensor near metallic surfaces, shelving, or other fixed obstructions that may interfere with detection accuracy.
- This guidance applies to both ULR and non-ULR versions.




Specifications

12-24Vdc		
<50mA		
IEC62386-104 over Thread®		
-20 to 55°C		
PC		
Class III		
Zhaga (Book 18) 40mm		
IP66		
IEC 61347-2-11 IEC 60950-1 EN 55015	IEC 62386-104 IEC 62386-103 EMC-2004/108/EC LVD-2006/95/EC	
	<50mA IEC62386-104 over Three -20 to 55°C PC Class III Zhaga (Book 18) 40mm IP66 IEC 61347-2-11 IEC 60950-1	

Wiring


Pin function

- 1 DC+ (12-24V) 2 0-10V Dim- / DC-
- 2 0-10 0 01111-7 00
- 3 Not used
- **4** 0-10V dim+



Detection pattern

Mounting height 3 - 15 m **Range ø** 8 m (mounted at 10 m)



Notice

Download the **zencontrol** Android app to configure your device.



Standalone

zencontrol Express



Full control zencontrol

zencontrol Commissioining